

FICHE TECHNIQUES

IETM NO.	PHOTO	SURFACE FINISH	MATERIAL	SIZE	INFORMATION
SAR 890(LD 13-1160X 600DTP)		POLISHED	SUS 304	1160X600X320MM	VOLTAGE: 220V(50Hz-60Hz) CURRENT: 12.0A TOTAL POWER: 125W HEATING : CARBON FIBER HEATING WIRE PLUG :EURO PLUG PROTECTION DEGREE: IPX4
SAR 890RG(LD 13-1160X 600DTR)		BRUSHED ROSE GOLD			
SAR 890G(LD 13-1160X 600DTG)		BRUSHED GOLD			
SAR 890B(LD 13-1160X 600DTB)		BLACK			
SAR 891(EL 13-740X 500DTP)		POLISHED	SUS 304	740X500X110MM	VOLTAGE: 220V(50Hz-60Hz) CURRENT: 12.0A TOTAL POWER: 80W HEATING : CARBON FIBER HEATING WIRE PLUG :EURO PLUG PROTECTION DEGREE: IPX4
SAR 891RG(EL 13-740X 500DTR)		BRUSHED ROSE GOLD			
SAR 891G(EL 13-740X 500DTG)		BRUSHED GOLD			
SAR 891B(EL 13-740X 500DTB)		BLACK			
SAR 892(EL 13-700X 500DWP)		POLISHED	SUS 304	700X500X230MM	VOLTAGE: 220V(50Hz-60Hz) CURRENT: 12.0A TOTAL POWER: 120W HEATING : CARBON FIBER HEATING WIRE PLUG :EURO PLUG PROTECTION DEGREE: IPX4
SAR 892RG(EL 13-700X 500DWR)		BRUSHED ROSE GOLD			
SAR 892G(EL 13-700X 500DWG)		BRUSHED GOLD			
SAR 892B(EL 13-700X 500DWB)		BLACK			
SAR 893(EL 13-1200X 500DTP)		POLISHED	SUS 304	1200X500X110MM	VOLTAGE: 220V(50Hz-60Hz) CURRENT: 12.0A TOTAL POWER: 156W HEATING : CARBON FIBER HEATING WIRE PLUG :EURO PLUG PROTECTION DEGREE: IPX4
SAR 893RG(EL 13-1200X 500DTR)		BRUSHED ROSE GOLD			
SAR 893G(EL 13-1200X 500DTG)		BRUSHED GOLD			
SAR 893B(EL 13-1200X 500DTB)		BLACK			